NetterVibration





Netter Fastening Sets for PKL Series NBS



- Safe and solid attachment of the PKL impactors
- Versions for threaded or clearance bores



NBS 740 for PKL 740



NBS 2100 for PKL 2100 or NBS 5000 for PKL 5000




NetterVibration




Netter Fastening Set for PKL Series NBS

Impactor Type	NBS Type	Fastening screws	Fastening plates thickness [mm]
PKL 740	NBS 740		
PKL 740	NBS G 740	M12x60	15
PKL 740	NBS D 740	M12x90	15
PKL 2100	NBS 2100		
PKL 2100	NBS G 2100	M12x50	15
PKL 2100	NBS D 2100	M12x90	15
PKL 5000	NBS 5000		
PKL 5000	NBS G 5000	M16x75	20
PKL 5000	NBS D 5000	M16x110	20

Mounting procedure using the example of the NBS 740 D on a PKL 740




Tighten the 4 bolts evenly crosswise until the distance is 14 mm between locking plate and housing center.




When using NBS D, the nuts must be locked after adjusting the distance.

The included screws are suitable for mounting plates with a thickness up to 15 mm.



Bend the locking tabs of the locking plate to the head of the screw, to secure the screw against rotation.



Applications:

The NBS fixing sets provide a safe and solid attachment of the PKL impactors.

NetterVibration provides on request, these NBS fixing sets (screws, springs, matching washers).

NetterVibration offers the accessories required fort the mounting, installation, control and monitoring of vibrators and impactors.

Netter provides solutions.

Consult our experienced application technicians.

Netter GmbH

Fritz-Lenges-Str. 3 55252 Mainz-Kastel

- Germany
- Switzerland
- Poland
- Spain
- Australia

www.**Netter**Vibration.com info@**Netter**Vibration.com